

DESCRIPTION

Päram Süper Primer is designed to be both a sealer and bonding agent for interior applications of the Päram 5500. It is a concentrated re-emulsifiable adhesive specifically designed to enhance the bond of the Päram 5500 providing maximum adhesion and seal between the substrate and the self leveling concrete.

ADVANTAGES

- Water based and VOC compliant
- Excellent coverage rate
- Odorless
- Non-flammable, non-toxic, non-explosive
- Creates an excellent bond
- High solids content
- Excellent bonding agent for increased adhesive strength

APPLICATION

SUBSTRATE REQUIREMENTS

- Clean the areas and remove all unsound concrete, grease, oil, paint, asphalt, tar and any other foreign materials that will inhibit performance
- Substrates must be stable, solid and structurally sound
- Substrate must be mechanically profiled by shot-blasting, sand blasting or scarifying to achieve a CSP 4 to CSP 5
- After cleaning and profiling, test for MVER (moisture vapor emission rate)
- For applications over cutback adhesive residue, wood surfaces, non-porous substrates such as terrazzo, ceramic and quarry tile, burnished concrete, epoxy coatings, painted surfaces and metal, please contact Duraamen's technical staff.

PRIMING

- *Päram Primer* must be applied over entire substrate that is at least at 50°F

or porous substrates 2 coats of Päram primer may be necessary.

- The primer is dilution @ 1:1 with clean potable water before applying on the surface. **Coverage:** 350-400ft²/ga
- The primer must be applied evenly with a fine hair push broom. DO NOT use paint rollers, mops, or spray equipment except over wood and metal (contact Duraamen technical staff for correct priming applications).
- Apply a thin primer layer leaving no bare spots, puddles or excess primer. Allow to dry to a clear, thin film.
- Important: *Päram 5500* must be applied within 48 hours of priming to insure that a good bond is achieved between primer and the substrate. It is very important that the primed substrate is not contaminated in any way prior to the installation of *Päram 5500*.

COVERAGE

Päram Süper Primer yields 350-400ft² per gallon when diluted with water at 1:1 ratio.

AVAILABILITY

Päram 5500 is available throughout the United States and Canada. Contact *Duraamen* representative in your area for details.

TECHNICAL SERVICE

Duraamen Building & Allied Products, Inc. provides services and consultations on material selection, specification, troubleshooting, and other information on the proper repair and protection of concrete surfaces.

TECHNICAL DATA

Density	8.9lb/ga
Coverage	350/400ft ² /ga diluted
Solids Content	54% by volume
Flash point	0
Drying time	2-3 hours @ 70F

WARRANTY

Duraamen Building & Allied products, Inc. warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed and applied in accordance with recommendations of *Duraamen*. If any product fails to meet this warranty, the liability of *Duraamen* will be limited to replacement of any non-conforming material if notice of such non-conformity is given to *Duraamen* within (1) one year of delivery of materials. *Duraamen* may in its discretion refund the price received by *Duraamen* in lieu of replacing the material. No customer, distributor or representative is authorized to change or modify the published specifications of this warranty in any way. No one is authorized to make oral warranties on behalf of *Duraamen*. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. *Duraamen* reserves the right to inspect the non-conforming material prior to replacement. EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE. DURAAMEN'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND DURAAMEN SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY OTHER THIRD PARTY FOR ANY LOSS, COST, EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Corporate office

Duraamen Building & Allied Products Inc. 457 Frelinghuysen Avenue, Unit 101, Newark, NJ 07114

T: 1.866.835.6595 | F: 1.866.629.4157

info@duraamen.com