

Bactoclean BC

Microbial, biocarbon floor cleaner for commercial kitchens

düraamen
engineered to perform

DESCRIPTION

Bactoclean BC is a powerful specially formulated cleaning solution based on oil eating microbial that is ideal for removing fats, oils, grease, protein, cellulose and starch. It assists on cleaning grease traps and septic tanks. Bactoclean BC is the perfect choice in restaurants of food producing facilities where drain lines and grease traps are a problem. It is also effective for cleaning slick floors and controlling odors as well as cleaning up blood, vomit and animal/human waste.

ADVANTAGES

- Safely removes fats, oils and grease from concrete or tile floors without etching.
- Excellent surface preparation cleaner for areas that are going to be sealed or coated with resinous flooring or concrete flooring systems.
- Can be used daily to clean oil from all types of surfaces especially where slip and fall issues can occur.
- Does not need to be neutralized.
- Degrades/eliminates organics that are found in drain lines and grease traps while also eliminating odors.
- Penetrates all cracks, crevices and pores of the various surfaces in bathrooms and kitchens where organics accumulate, leaving them visually cleaner.
- Bactoclean BC provides long term odor control by removing the organics that cause odors and prevent the return of odor causing compounds.
- Eliminates the need for excessive pumping in septic tanks and waste treatment facilities. The microbes will consume toilet tissue, hair, starches and proteins that cause the tank drain fields to become plugged.

STORAGE

Bactoclean BC has a shelf life of 2 years. Close the container tightly after each use. Store in original container only. Store and use in temperatures between 40 and 120°F. DO NOT allow to freeze.

WARRANTY

Information regarding Duraamen products is based upon extensive research provided by the supplier of the raw materials. By making such information available, Duraamen Engineered Products Inc. does not assume any liability beyond express terms of our standard limited material warranty. Duraamen Engineered Products does not warrant the accuracy or completeness of any such information, whether conveyed orally or in writing, but to the best of our knowledge believe it to be accurate. We reserve the right at any time and without notice to update or improve our products and process for the intended use or application. Duraamen Engineered Products (Duraamen) warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed and applied in accordance with recommendations of Duraamen. If any product fails to meet this warranty, the liability of Duraamen will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Duraamen within 1 (one) year of delivery of materials. Duraamen may in its discretion refund the price received by Duraamen in lieu of replacing the material. No customer, distributor, or representative of Duraamen is authorized to change or modify the published specifications of this warranty in anyway. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. Duraamen reserves the right to inspect the non-conforming material prior to replacement EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR PURPOSE. DURAAMEN'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND DURAAMEN SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

COVERAGE

150 to 300 sq. ft per gallon depending on contamination and dilution rate.

APPLICATION

1. Dilute with water - 1 part Bactoclean to 3 parts water
2. Spray water on the surface that needs to be cleaned. Subsequently spray Bactoclean BC on the entire surface.
3. Agitate the surface with a stiff bristle broom or mechanical scrubber. This agitation is essential to break down the oil and dirt for faster digestion and cleaning. Agitate the area periodically and keep the area moist while the bacteria are working. DO NOT let the area dry out!

Dwell Time


- Daily Cleaning: 10–15 minutes
 - Surface prep before installing a resinous floor: 2–3 hours
 - Surfaces that have been exposed to oil for a long period of time may require longer dwell times for the microbes to completely clean and digest all the contamination.
4. After the surface is free from biocarbon contamination, rinse thoroughly with clean lukewarm water into a drain or wet vacuum the residual liquid.
 5. Bactoclean BC does not contain caustics or acids so it does not need to be neutralized. It does not leave any chemical residue.

AVAILABILITY

Bactoclean BC is available throughout the United States and Canada. Contact Düraamen representative in your area for details.

TECHNICAL SERVICE

Düraamen Engineered Products, Inc. provides services and consultations on material selection, specification, troubleshooting, and other information on the proper repair and protection of concrete surfaces.



düraamen engineered products, inc.

20 Haypress Road, Suite 323 Cranbury, NJ 08512 | duraamen.com | info@duraamen.com | 1.866.835.6595