

# Bactoclean HC

Industrial-strength, microbial cleaner for oil & fuel-stained concrete.



## DESCRIPTION

Bactoclean HC is a powerful cleaning solution based on oil eating microbial that is ideal for removing dirt and remediating all types of hydrocarbon-based products. It will remove oils, fuels, grease/lubricants in a variety of applications where removing of these substances is to challenge to remove.

## ADVANTAGES

- Effectively cleans oils, fuels, solvents and grease/lubricants from concrete, tile, plastic and wood.
- Excellent surface preparation cleaner for areas that are going to be sealed or coated with resinous flooring or concrete flooring systems.
- Can be used daily to clean oil from all types of surfaces especially where slip and fall issues can occur.
- Does not need to be neutralized.
- It can be used clean metal surfaces where oil hinders repainting.
- Does not cause corrosion to metals.
- Safe to use on fiberglass or plastics.
- Does not etch or damage concrete or coatings.

## STORAGE

Bactoclean HC has a shelf life of 2 years. Close the container tightly after each use. Store in original container only. Store and use in temperatures between 40 and 120°F. DO NOT allow to freeze.

## COVERAGE

150 to 300 sq. ft per gallon depending on contamination and dilution rate.

## WARRANTY


Information regarding Düraamen products is based upon extensive research provided by the supplier of the raw materials. By making such information available, Düraamen Engineered Products Inc. does not assume any liability beyond express terms of our standard limited material warranty. Düraamen Engineered Products does not warrant the accuracy or completeness of any such information, whether conveyed orally or in writing, but to the best of our knowledge believe it to be accurate. We reserve the right at any time and without notice to update or improve our products and process for the intended use or application. Düraamen Engineered Products (Düraamen) warrants for a period of one (1) year that its products will be free of manufacturing defects and will be in conformity with published specifications when handled, stored, mixed and applied in accordance with recommendations of Düraamen. If any product fails to meet this warranty, the liability of Düraamen will be limited to replacement of any non-conforming material if notice of such non-conformity is given to Düraamen within 1 (one) year of delivery of materials. Düraamen may in its discretion refund the price received by Düraamen in lieu of replacing the material. No customer, distributor, or representative of Düraamen is authorized to change or modify the published specifications of this warranty in anyway. In order to obtain replacement or refund the customer must provide written notice containing full details of the non-conformity. Düraamen reserves the right to inspect the non-conforming material prior to replacement EXCEPT FOR THE EXPRESSED WARRANTY STATED ABOVE, THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR PURPOSE. DÜRAAMEN'S OBLIGATION SHALL NOT EXTEND BEYOND THE OBLIGATIONS EXPRESSLY UNDERTAKEN ABOVE AND DÜRAAMEN SHALL HAVE NO LIABILITY OR RESPONSIBILITY TO THE PURCHASER OR ANY THIRD PARTY FOR ANY LOSS, COST EXPENSE, DAMAGE OR LIABILITY, WHETHER DIRECT OR INDIRECT, OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

## APPLICATION

1. Dilute with water - 1 part Bactoclean to 3 parts water
  2. Spray water on the surface that needs to be cleaned. Subsequently spray Bactoclean HC on the entire surface.
  3. Agitate the surface with a stiff bristle broom or mechanical scrubber. This agitation is essential to break down the oil and dirt for faster digestion and cleaning. Agitate the area periodically and keep the area moist while the bacteria are working
- Dwell Time**
- Daily Cleaning: 10–15 minutes
  - Surface prep before installing a resinous floor: 2–3 hours
  - Surfaces that have been exposed to oil for a long period of time may require longer dwell times for the microbes to completely clean and digest all the contamination.
4. After the surface is free from oil contamination, rinse thoroughly with clean lukewarm water to a drain or wet vacuum the residual liquid.
  5. Bactoclean HC does not contain caustics or acids so it does not need to be neutralized. It does not leave any chemical residue.

## TECHNICAL SERVICE

Düraamen Engineered Products, Inc. provides services and consultations on material selection, specification, troubleshooting, and other information on the proper repair and protection of concrete surfaces.



düraamen engineered products, inc.

20 Haypress Road, Suite 323 Cranbury, NJ 08512 | [duraamen.com](http://duraamen.com) | [info@duraamen.com](mailto:info@duraamen.com) | 1.866.835.6595